



MODEL No.	DESCRIPTION*	POWER REQUIREMENTS
SL441-RT	4 X 100 Watts	32 Amps, 12VDC
SL422-RT**	2 X 150 Watts	24 Amps, 12VDC
SL442-RT**	4 X 150 Watts	48 Amps, 12VDC

\*\* Available in both Metal Halide(MH) and LED options  
 LED adds 3lbs/ head to weight and width becomes 32"  
 MH adds 5lbs/ head to weight and height becomes 10"

MODEL No.	DESCRIPTION*	POWER REQUIREMENTS
SL443-RT	4 X 350 Watts	1.5 KW, 110 or 220VAC
SL445-RT	4 X 500 Watts	2.0 KW, 110 or 220VAC
SL429-RT	2 X 1500 Watts	3.0 KW, 220VAC

\*Lumens per light head: 100W=2500/150W MH=11,250  
 150W LED=12,000 / 350W HIR=10,000 / 500W=11,100 / 1500W=35,800  
 (Note: 350W, 650W, 900W HIR not for use on PTO Generators)



Strobe



SL441



2 x 1500 Watt

## OPTIONS

- TOP MOUNTED STROBE
- PANEL MOUNTED CONTROLS
- OPTIONAL 80" UNIT
- 2 OR 4 LIGHT FIXTURES
- LAMPS 100W TO 1500W
- LED, METAL HALIDE, & XENON



Havis Shield



FRC Optima



Xenon



LED

Whelen Pioneer Plus

## SHADOW-RT FEATURES:

- FULL DEPLOYMENT IN UNDER 15 SECONDS
- ALL WEATHER (not affected by ice buildup, high winds, blowing dust)
- ABILITY TO OVERHANG EDGE OF VEHICLE
- UMBILICAL REMOTE CONTROLLER WITH 15' CORD
- ALL ELECTRIC (No air or hydraulics required)
- SHADOW-RT ROTATES 355°
- MAINTENANCE FREE
- FIVE YEAR WARRANTY
- NFPA 1901 COMPLIANT
- TESTED TO 90 MPH WIND

The advantage of an electrically deployed tower is speed. In under 15 seconds you can have the tower fully set-up and be helping on the scene. That is just not possible with manual pole lights.



LIGHTING 101

